



Overview

Lifting plugs for drilling-tool handling and cross-over subs for connecting different drilling components.

Selection

Select by equipment model, pipe diameter, rated load or torque, and connection dimensions. Check each size within the same series separately.

Lifting Plugs

Thread	O.D. (mm)	Length (mm)	Thread	O.D. (mm)	Length (mm)
7-5/8 REG Pin	Φ210	290	7-5/8 REG Pin	Φ230	290
6-5/8 REG Pin	Φ190	280	6-5/8 REG Pin	Φ200	280
NC50 Pin	Φ155	270	NC50 Pin	Φ160	260
NC46 Pin	Φ150	270	NC46 Pin	Φ160	260
NC38 Pin	Φ115	260	NC38 Pin	Φ120	270
NC31 Pin	Φ100	210	NC31 Pin	Φ120	220
2-3/8 REG Pin	Φ80	190	2-3/8 REG Pin	Φ110	200
NC26 Pin	Φ89	200	NC26 Pin	Φ110	200
3-1/2 REG Pin	Φ100	220	3-1/2 REG Pin	Φ130	270
4-1/2 REG Pin	Φ145	260	4-1/2 REG Pin	Φ160	260
2-7/8 REG Pin	Φ80	220	2-7/8 REG Pin	Φ80	220

Cross-over Subs

S/N	Name	Upper Connecting Piece	Lower Connecting Piece	Model
1	Square kelly cross-over sub	Square kelly	Drill Pipe	A or B
2	Drill pipe cross-over sub	Drill Pipe	Drill Pipe	A or B
3	Transition cross-over sub	Drill Pipe	Drill collar	A or B
4	Drill collar cross-over sub	Drill collar	Drill collar	A or B
5	Drill bit cross-over sub	Drill collar	Drill bit	A or B
6	Swivel cross-over sub	Swivel lower sub	Square kelly	C
7	Cross-over sub for fishing	Square kelly	Drill Pipe	c
		Drill Pipe	Fishing tools	c

Exterior view of cross-over subs

